

Exhaust Rail System 920



Easy to handle systems for all types of workshops. Consists of a basic rail system which is completed with an exhaust extraction unit. Very high extraction efficiency. One extraction unit can serve several workbays. Extraction units are easy to move, thanks to light-weight material and ball bearing wheels. Two 400 units serve cars with twin exhaust pipes. Manual disconnection of exhaust nozzles.

For choice of nozzles, see page Exhaust Nozzles.

- Compact, modern design
- Easy to move and position
- Automatic damper for airflow control
- Quick and simple installation reduces cost



Rail kit 920**

Length, m (ft.)	Part no.
2.5 (8)	20916020
5 (16)	20916120
7.5 (25)	20916220
10 (33)	20916320
12.5 (41)	20916420
15 (50)	20916520
17.5 (57)	20916620
20 (66)	20916720
22.5 (74)	20916820
25 (82)	20916920
27.5 (90)	20917020
30 (98)	20917120
35 (115)	20917220
40 (141)	20917320
45 (148)	20917420
50 (164)	20917520

Exhaust Extraction unit with trolley, hose

Trolley	Hose Ø, mm (in.)	Hose type*	Hose length, m (in.)	Nozzle storage	Balancer	Damper	Hose suspension	Part no.
400	100 (4)	NR-B	5.0 (16)	X		X		20915720
400	100 (4)	NR-CP	5.0 (16)	X		X		20915220
400	100 (4)	NR-B	7.5 (25)	X		X		20915120
400	100 (4)	NR-B	5.0 (16)		X	X		20915620
400	100 (4)	NR-CP	5.0 (16)		X	X		20915520
400	100 (4)	NR-B	7.5 (25)		X	X		20915020
1500	150 (6)	NR-CP	5.0 (16)		X	X	X	20914020
1500	150 (6)	NR-B	5.0 (16)		X	X	X	20914120
1500	150 (6)	NR-CP	5.0 (16)	X		X		20914320
1500	150 (6)	NR-B	5.0 (16)	X		X		20914420

Accessories	Rail kit	For 400-trolley	For 1500-trolley	Part no.
Top connection. Outlet: Ø 200 mm (8 in.)	X			20374246
Damper, Ø 100 mm (4 in.)		X		20373752
Damper, Ø 160 mm (6 in.)			X	20373796
Balancer kit		X		20373759
Safety coupling, Ø 100 mm (4 in.)		X		20374541
Safety coupling, Ø 150 mm (6 in.)			X	20374543

* Hose type - see separate section

** Complete with suspension parts, joint connectors, rubber seals, end covers and end stops.

For rail lengths > 50 m (154 ft.), please contact your local Nederman dealer.

Product availability may differ by country