

# Fume Extractor on Rail



The Nederman fume extractor trolley with extractor arm, is intended to be used in combination with the rail Nederman ALU 150 when extraction from long working areas is required.

- One extraction arm can serve several work places
- The trolley is easily moved along the rail
- The trolley fits Nederman extraction arms shown below

Description	Length, m (ft.)	Part no.
Trolley		20940210
Rail stiffener, one pc per metre (39 inches) of rail		20373942
Straight rail ALU 150*	2.5 (8)	20900510
Straight rail ALU 150*	5.0 (16 1/2)	20900610
Straight rail ALU 150*	7.5 (24)	20900710
Straight rail ALU 150*	10.0 (32)	20900810
Straight rail ALU 150*	12.5 (41)	20900910
Straight rail ALU 150*	15.0 (49)	20901010
Straight rail ALU 150*	17.5 (57)	20901110
Straight rail ALU 150*	20.0 (65)	20901210
Straight rail ALU 150*	22.5 (73)	20901310
Straight rail ALU 150*	25.0 (82)	20901410
Straight rail ALU 150*	27.5 (90)	20901510
Straight rail ALU 150*	30.0 (99)	20901610
Straight rail ALU 150*	35.0 (114)	20901710
Straight rail ALU 150*	40.0 (131)	20901810
Straight rail ALU 150*	45.0 (147)	20901910
Straight rail ALU 150*	50.0 (164)	20902010

\* Including rubber lips, joint connectors, suspension brackets, limit stops and end covers.  
For rail lengths > 50 m (164 ft.), please contact your local Nederman dealer.

Accessory	Part no.
Top outlet Ø, 200 mm (8 inch)	20940410

Recommended extraction arms	
Extraction Arm Original	Maximum 4 m (14 ft.)
Extraction Arm Telescopic	All models
Extraction Arm NEX MD	Maximum 3 m (10 ft.)
Extraction Arm NEX HD	Maximum 3 m (10 ft.)

Product availability may differ by country